SAFETY DATA SHEET

CONTACT SPRAY ADHESIVE- TPO/EPDM



SECTION 1- PRODUCT AND COMPANY IDENTIFICATION

1.1 Product Identifier

Product Name: Polyset TPO/EPDM Spray Contact Adhesive

Product Item Number: P11500 SDS ID Number SD024

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use Spray Adhesive

Uses advised against

1.3 Details of the supplier and of the safety data sheetManufacturer ICP Building Solutions Group

2775 Barber Road Norton, Ohio 44203

In Ohio: 330-753-4585; 1-800-321-5585 (Monday-Friday 8:00am-5:00pm EST)

1.4 Emergency telephone numbers

In the U.S.A CHEMTEL (24 hours) 1-800-255-3924 International Emergency CHEMTEL (24 hours) 1-813-248-0585

SECTION 2- HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Product definition: Mixture

Classification:

Flammable Liquid- Category 2

Gases Under Pressure- Compressed Gas Acute Toxicity Inhalation- Category 4 Serious Eye Irritation- Category 2A Specific Target Organ Toxicity SE 3 Aquatic Hazard-Chronic Category 3

2.2 Label elements

Hazard Symbols:



Signal Word: WARNING

Hazard Statements: H280- Contains gas under pressure; may explode if heated

H225- Highly flammable liquid and vapours

H302- Harmful if swallowed H312- Harmful in contact with skin H319- Causes serious eye irritation

H332- Harmful if inhaled

H336- May cause drowsiness or dizziness

H412- Harmful to aquatic life with long lasting effects

Prevention: P202- Do not handle until all safety precautions have been read and understood

P210- Keep away from heat, sparks, open flames and hot surfaces. No smoking

P251- Pressurized Container: Do not pierce or burn, even after use

P262- Do not get in eyes, on skin, or on clothing

P273- Avoid release to the environment

P280- Wear protective gloves, protective clothing and eye protection

Response: P302+P352+P333+P313 IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get

medical attention

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing

P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. P314- Get medical advice if you feel unwell

P342+P311- If experiencing respiratory symptoms: Call a POISON CENTER or doctor

TPO/EPDM ADHESIVE ISSUE DATE: October 2019 LAST REV: July 2020 PAGE 2 OF 6

P381- Eliminate all ignition sources if safe to do so

Storage: P403+P405- Store in a well-ventilated place. Store locked up.

P410- Protect from sunlight

P412- Do not expose to temperatures exceeding 50°C/122°F.

Disposal: P501 Dispose of contents/container in accordance with applicable local/regional/national/international

regulations.

SECTION 3- COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	Ingredient	CAS No.
30-60	Methyl Acetate	79-20-9
10-25	Isopentane	109-66-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to the health or the environment and hence require reporting in this section.

SECTION 4- FIRST AID MEASURES

4.1 Description of first aid measures

Eye: Immediately flush eyes with large amounts of water for at least 15 minutes, holding the eyes open with fingers and

occasionally lifting the upper and lower lids. Use lukewarm water if possible. If present and easy to do so, remove contact

lenses, If irritation persists, get medical attention.

Skin: In case of contact, immediately flush skin with plenty of soap and water. Foam will stick to skin, gently wipe product from skin

with a damp cloth and wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash clothing before

reuse. Call a physician if irritation persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Obtain medical

attention.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an

unconscious person. Get medical advice/attention.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3 Notes to the physician

Symptoms may not appear immediately. If case of an accident or if you feel unwell, seek medical advice immediately (show label or SDS if possible).

SECTION 5- FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable methods of extinction: Use dry chemical, carbon dioxide, foam, Halon 1211 and water spray or fog. **Unsuitable methods of extinction**: Do not use water jets and high pressure water as these may spread the fire

5.2 Special hazards arising from the substance or mixture

Contains compressed gas/chemicals under pressure. Eliminate all ignition sources. Closed cylinders may explode due to buildup of pressure when exposed to extreme heat. Cylinders exposed to fire or high temperature can rupture and rocket. Cured adhesive will burn in the presence of heat, oxygen and an ignition source. Highly toxic gases may be generated by thermal decomposition or combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent or may be delayed. Hazardous decomposition products may include and are not limited to: Carbon monoxide, Carbon dioxide, Aldehydes, Oxides of Nitrogen.

5.3 Advice to firefighters

Keep upwind of fire. Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Containers may explode if heated.

SECTION 6- ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2 Environmental precautions

Do not allow to enter sewers, drains, or waterways

TPO/EPDM ADHESIVE ISSUE DATE: October 2019 LAST REV: July 2020 PAGE 3 OF 6

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up: Scoop up material and place in a disposal container. Dispose of as plastic waste in accordance with all applicable guidelines and regulations. Vapors can accumulate in low areas. Provide ventilation.

6.4 Reference to other sections

For indications about waste treatment & disposal, see Section 13.

For handling & storage, see Section 7.

SECTION 7- HANDLING AND STORAGE

7.1 Precautions for safe handling

Pressurized container: do not pierce or burn, even after use. Container may explode if heated. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Do not swallow. Use only in a well-ventilated area or outdoors. When using do not eat, drink or smoke. (See section 8)

General hygiene advice: Launder contaminated clothing before reuse. Wash hands before eating, drinking or smoking.

7.2 Conditions for safe storage including any incompatibilities

Store in a dry place. Ideal use temperature is 65°F to 80°F (18°C to 27°C). Do not expose cylinders to open flame or store at temperatures above 122°F (50°C). Excessive heat can cause premature aging of components resulting in a shorter shelf life. Storage below 55°F (12.7°C) may affect foam quality if chemicals are not warmed to room temperature before using. Protect containers from physical abuse. Keep cylinders upright. **KEEP AWAY FROM CHILDREN.**

SECTION 8- EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control Parameters

CAS No.	Ingredient	OSHA-PEL TWA	ACGIH-TLV	NIOSH/ Other
79-20-9	Methyl Acetate	200 ppm; 610 mg/m ³	200 ppm; 610 mg/ m³ (8 hours) TWA	STEL 250 ppm
109-66-0	Pentane		600 ppm (8 hours) TWA	

8.2 Exposure Controls:

Engineering measures: Use ventilation adequate to keep exposures below recommended exposure limits.

Eye/face Protection: Wear protective safety glasses with side shields or goggles.

Hand Protection: Use chemically resistant gloves (i.e. Nitrile gloves). Nitrile/butadiene rubber, butyl rubber, polyethylene, PVC (vinyl), or neoprene gloves are also effective. Glove selection should take into account potential body reactions to certain materials and manufacturer's instructions for use. Break through time of selected gloves must be greater than the intended use period.

Other Protective Equipment: Use clothing that protects against dermal exposure. Appropriate protective clothing varies depending on the potential for exposure. To ensure proper skin protection, wear PPE in such a manner that no skin is exposed.

Respiratory Protection: If atmospheric levels are expected to exceed the exposure levels, use a NIOSH approved air purifying respirator equipped with an organic vapor cartridge and particulate filter. If atmospheric levels exceed 10 times the TLV or PEL level for which an airpurifying respirator is effective, use a powered air purifying respirator (PAPR). The type of respiratory protection selected must comply with the requirements set forth in OSHA's Respiratory Protection Standard (29 CFR 1910.134).

Hygiene Measures: An eye wash station or portable eye wash station should be in the area. Wash hands thoroughly after use, before eating, drinking or using the lavatory. Employees/Users should be educated and trained in the safe use and handling of this product.

SECTION 9- Physical and chemical properties

9.1 Information on basic physical and chemical properties				
General Physical Form	Viscous liquid which forms clear adhesive upon release.			
Color	Clear. Some products contain a dye or colorant.			
Odor	Slight odor during curing stage			
Odor Threshold:	No data available			
Physical State:	Gas/Pressurized Liquid/Semi-Solid			
pH:	No data available			
Melting Point/Freezing Point	No data available			
Initial Boiling Point and Boiling Range	No data available			
Flash Point:	-20F			
Evaporation Rate:	No data available			
Flammability:	Flammable			

TPO/EPDM ADHESIVE ISSUE DATE: October 2019 LAST REV: July 2020 PAGE 4 OF 6

Lower Flammability/Explosive Limit:	No data available
Upper Flammability/Explosive Limit:	No data available
Vapor Pressure	No data available
Vapor Density:	Not available
Relative Density/Specific Gravity:	~ 0.887 (Water = 1)
Solubility:	Slightly soluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition Temperature:	No data available
Decomposition Temperature;	No data available
Viscosity:	No data available
Oxidizing Properties:	No data available
VOC Content (Calculated)	75 g/l

SECTION 10- STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical Stability

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not pierce or burn, even after use. Avoid temperatures below 40°F (4°C). For longest shelf life, avoid storage above 100°F (38°C).

10.3 Possibility of Hazardous Reactions

Elevated temperatures can cause product to decompose, releasing carbon dioxide. Flammable propellant. Contents are under pressure and exposure to high temperature can cause containers to rupture or explode.

10.4 Conditions To Avoid

Heat. Incompatible materials. Sources of ignition. Avoid temperatures below 40°F (4°C) or temperatures above 100°F (38°C).

10.5 Incompatible Materials

Alcohols, strong bases, amines, metal compounds, ammonia, and strong oxidizers.

10.6 Hazardous Decomposition Products

See Section 5.2 for hazardous decomposition products due to combustion.

SECTION 11- TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure based on test data and/or information on the components, this material may produce the following health effects:

Eye: May cause eye irritation. **Skin:**May cause skin irritation.

Inhalation: May be harmful if inhaled. May cause respiratory irritation. Inhalation of large quantities may cause: Dizziness, euphoria,

agitation, convulsions, and narcosis.

Ingestion: May be harmful if swallowed. May cause gastrointestinal irritation: stomach distress, nausea, or vomiting.

Acute Oral Toxicity

Expected to have low acute oral toxicity

Acute inhalation toxicity

Expected to have low acute inhalation toxicity

Acute dermal toxicity

Expected to have low acute dermal toxicity

Skin irritation

Causes skin irritation

Eye irritation

Causes serious eye irritation

Sensitization

May cause skin and respiratory sensitization

Genotoxicity

No data available

Mutagenicity

Data for Pentane: In vitro- Negative Ames Test

Specific organ toxicity- single exposure

May cause respiratory irritation

Specific organ toxicity- repeated exposure

May cause damage to the lungs, central nervous system and skin

TPO/EPDM ADHESIVE ISSUE DATE: October 2019 LAST REV: July 2020 PAGE 5 OF 6

Aspiration hazard

Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis

11.2 Delayed, Immediate, and Chronic Effects of Short- and Long-Term Exposure

Other: This product has not been tested. The above information has been derived from the properties of the individual components.

SECTION 12- ECOLOGICAL INFORMATION

12.1 Ecotoxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other Adverse Effects

No data available

SECTION 13- DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Methods of disposal

Before disposing of containers, relieve container of any remaining adhesive and pressure. Allow dispensed product to fully cure before disposing. Never discard in a liquid state. This material must be disposed of in accordance with all local, regional, national, international regulations.

Other disposal recommendations:

Do not puncture or incinerate containers. Use appropriate Personal Protective Equipment.

SECTION 14- TRANSPORTATION

Shipping Information

Ground	UN3501 Chemical Under Pressure, flammable n.o.s (Methyl Acetate, Pentane) 2.1 (Flammable Gas Label)
Air	UN3501 Chemical Under Pressure, flammable n.o.s (Methyl Acetate, Pentane) 2.1 (Flammable Gas Label)
Water	UN3501 Chemical Under Pressure, flammable n.o.s (Methyl Acetate, Pentane) 2.1 (Flammable Gas Label)

SECTION 15- REGULATORY

15.1 Safety, health, and environmental regulations/ legislations specific for the substance or mixture U.S. Federal Regulations

OSHA Hazard Communication Standard: This material is classified as a hazardous in accordance with OSHA 29 CFR 1910-1200 **TSCA Status**: All components of this product are listed on the Toxic Substance Control Act (TSCA) Inventory. This product is not subject to TSCA 12(b) Export Notification.

Superfund Amendments and Reauthorization Act (SARA)

SARA Section 311/312 Hazard Categories: Acute Health Hazard, Chronic Health Hazard, Reactive Hazard, Sudden Release of Pressure Hazard

SARA 313 Information: MDI and PMDI are subject to reporting levels established by Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986.

SARA 302/304 Extremely Hazardous Substance: No components of the product exceed the threshold (de minimis) reporting levels established by these sections of the Title III of SARA.

TPO/EPDM ADHESIVE ISSUE DATE: October 2019 LAST REV: July 2020 PAGE 6 OF 6

SARA 302/304 Emergency Planning & Notification: No components of the product exceed the threshold (de minimis) report levels established by these sections of the Title III of SARA.

U.S. State Regulations:

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: Components are listed Other U.S. State Inventories:

Right-to-Know lists and/or Air Quality/air Pollutants lists: CA, MA, NJ, PA

Global Chemical Inventory Lists:

United States: Toxic Substance Control Act (TSCA)- Yes

Canada: Domestic Substances List (DSL)- Yes Canada: Non-Domestic Substances List (NDSL)- No

15.2 Chemical safety assessment: For this product a chemical safety assessment was not carried out

SECTION 16- OTHER









NFPA: Health Hazard 2; Flammability 4; Reactivity 1 HMIS: Health Hazard 2; Flammability 4; Physical Hazard 1

Hazard Rating: 0=minimal, 1= slight, 2=moderate, 3=severe, 4= extreme

The information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof. The manufacturer makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties, either expressed or implied, of merchantability or fitness for a particular use are made hereunder with respect to this information or the product to which information refers.

Information contained herein is deemed to be reliable, conservative and accurate. ICP Building Solutions Group reserves the right to change the design, specifications or any other features at any time and without notice, while otherwise maintaining regulatory compliance.

Revision- July 24, 2020 (Date of Preparation) Version 1.2 Replaces April 2, 2020 Version 1.1